

Driver Info

Type:	Constant Current
120V:	Yes
277V:	N/A
480V:	N/A
Input Watts:	30W
Efficiency:	70%

LED Info

Watts:	30W
Color Temp:	5000K
Color Accuracy:	80CRI
L70 Lifespan:	50000
Lumens:	2000
Efficacy:	70LPW

Suitable for wet location and operation in ambient not exceeding 40 °C(104°F)
 Products are not intended for use in environments containing airborne corrosive
 airborne corrosive agents such as chemical.

Color: Bronze

Weight: 0.934Kg (2.06lbs)

FEATURES

- Description: 30W Wall-Mounted LED Barn Light
- Universal 120V
- Mercury Free: no UV
- Heavy-duty cast aluminum housing; rust and corrosion proof; polyester powder coating
- Standard pole mount compatible
- Dusk to Dawn with photo control
- 4KV surge protector inside of power supply
- IES/LM79/LM80 data available
- 5 Year Limited Warranty
- Mounting: wall mounting
- Application: yard, dock, backyard, barns, farms, alleyways, roadway, parking lots, sidewalk, porch, building wall, etc.

CONSTRUCTION

- Heavy-duty cast aluminum housing; rust and corrosion proof; polyester powder coating
- Diffuser: High light transmittance & Polycarbonate with UV
- Photo control: Electrical type with 120V
- LEDs: Top grade LED, high-output, long-life;
- Heat Sink: Aluminium sink attached to the housing directly to reduce LED heats and add to life
- LED Driver: Constant current
- Finish: Bronze finish. Environmentally friendly polyester powder coatings.
- Mounting: Standard hole for the 1-1/2"(40mm) pole mount

SPECIFICATION

General Performance

Input Wattage: **30W**, Lumens: **2000**, Efficacy: **70LPW**, Input Voltage: **120V/50-60HZ**, CRI: **>80**, CCT: **5000K**, Power Factor: **≥0.9**, THD: **≤20%**, Driver Type: **Constant Current / Class 1**, Surge Protector: **4KV inside of Driver**, Luminaire Life: **50000hrs**;

Physical

Dimension: **16.8"x9.3"x8.6"(427x237x220mm)**, Weight: **2.06lbs(0.934Kg)**;


Operation Condition

Operating Temperature: **-40°F~+104°F(-40°C-40°C)**, Humidity: **≤95%**;

Certificate

Certification: **ES2.0/4.1/4.2**, Environment: **Suitable for Wet Location**, Material: **Rohs compliant**.

Order Information



- 3000K
- 4000K
- 5000K

